[Type here]









ASP116 EVOLUTION CONTROLLER FOR HYDRAULIC

Modernize your existing lift with an ASP116 controller

Microprocessor based controller Speed up to 1m/s SD CARD for configuration, updating & fault logging Up to 6 floors with travelling cables to suit 15 meters of travel Control – APB, Down Collective, Full collective and Multiplex up to 3 lifts

Floor	Power 400V	15Kw 31A	22 Kw 50A
2 to 6 floors		£4,360.00	£4,672.00



Alternative door operator upon request Evolution Hydraulic prices 24/01/23 GBP's ASP116 Evolution Stand Alone Controller

BUS CAN communication between fully pre wired Car Top Box & controller

SD CARD technology for configuration, updating & fault history

MP3 voice synthesizer fully EN81 part 70 compliant

Absolute encoder with metal belt and brackets

Shaft wiring for 6 stops with BUS CAN SP228's, safety chain, locks and LOP's

Limit switches, ramps and brackets

6m trunking

Open Protocol (no programming tool required)

Prepared for single entrance 220 or 380v (adaptable to VVVF , VVVF Busmatic , 3 phase)

Prepared for solenoid & ramp voltage 48, 70, 110, 220 volt DC / AC

Power cable for motor

LIFT & CONTROLLER PRODUCTS LTD

54 Station Road Alderholt Fordingbridge Hampshire SP63RB

www.liftcontroller.co.uk

[Type here]